



## Product certificate K6266/03

Issued 2018-10-01

Replaces 2007-07-01

Page 1 of 3

### Sanitary tapware; single taps and mixer taps

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

#### Vola a/s

as specified in this product certificate and marked with the Kiwa<sup>®</sup>-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K652/03 "Sanitary tapware; single taps and mixer taps" dated d.d. 01-02-2012.

which covers the requirements of

EN 200:2008

"Sanitary tapware: Single taps and combination taps for water supply systems of type 1 and type 2 – General technical specification".

Luc Leroy  
Kiwa

*Publication of this certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

CERTIFICATE

#### Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00

Fax +31 88 998 44 20

[info@kiwa.nl](mailto:info@kiwa.nl)

[www.kiwa.nl](http://www.kiwa.nl)

#### Company

Vola a/s

Lunavej 2

8700 HORSENS

Denemarken

Tel. +45 7023.5500

Fax. +45 70235511

E-mail [sales@vola.dk](mailto:sales@vola.dk)

Internet [www.vola.dk](http://www.vola.dk)

Certification process  
consists of initial and  
regular assessment of:

- quality system
- product

## Sanitary tapware; single taps and mixer taps

---

### Technical specification

#### The products mentioned below belong to this certificate

---

##### Showermixer

600 – combination, concealed with diverter

700 -- combination, concealed

800 -- combination, concealed with diverter

1500 -- combination, concealed

1641 T8 – with diverter

1671

##### Sinkmixer

KV 3,

KV 4,

KV 6

KV 7.

##### Basinmixer

HV 5,

HV 6

HV 7.

##### Bathmixer

1611

1621

##### Single taps

S 50,

RB 1

RB 4

900 - combination, concealed

---

## Sanitary tapware; single taps and mixer taps

---

### Application and use

The sanitary taps "single taps and mixer taps" are intended for application in drinking water installations with a static waterpressure of maximum 1000 kPa, a minimum dynamic pressure of 50 kPa and a maximum watertemperature of 90°C.

The recommended limits for correct operation are a dynamic pressure between 100 kPa and 500 kPa and a water temperature of maximum 65°C.

### Marking

The products are marked with the wordmark "KIWA" and the abbreviated wordmark "KK" in a rectangle.

Place of the mark:

- "KIWA" on the taphouse,
- "KK" on the headpart(s).

Additional compulsory specifications:

- name or mark of manufacturer: on the taphouse an headpart(s);
- indication for the watertemperature: on the controlknobs;
- identification of the accoustic group if classified, on the body;
- identification of the flow resistance class, on the body.

Method of marking:

- Non-erasable;
- visible after assembly.

### RECOMMENDATIONS FOR CUSTOMERS

**Check at the time of delivery whether:**

- **the supplier has delivered in accordance with the agreement;**
- **the mark and the marking method are correct;**
- **the products show no visible defects as a result of transport etc.**

**If you should reject a product on the basis of the above, please contact:**

- **Vola a/s**
- and, if necessary,**
- **Kiwa Nederland B.V.**

**Consult the supplier's processing guidelines for the proper storage and transport methods.**