



Product certificate K6127/05

Issued 2020-06-15

Replaces K6127/04

Page 1 of 3

Float operated valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

WERIT Kunststoffwerke W.Schneider GmbH & Co. KG

as specified in this product certificate and marked with the Kiwa[®]-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K615 "Float operated valves for flushing cisterns" dated 15-09-2019.

which covers the requirements of

EN14124: 2004 "Inlet valves for flushing cisterns with internal overflow".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

286180711

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Company

WERIT Kunststoffwerke W.Schneider GmbH & Co. KG
Industriepark Nord 27
53567 BUCHHOLZ-MENDT
Germany
Tel. +49 (0)2683 97 60
info@jomo.de
www.jomo.de



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Float operated valves

PRODUCT SPECIFICATION

The products mentioned below belong to this -product certificate

- a. Low noise float valve JOMO Lokus Pokus Art. No. 477000
with Styrofoam float and adjustable shut off water level from
30 up to 94 mm.

- b. Low noise float valve JOMO Lokus Pokus Art. No. 488000
with PE float and adjustable shut off water level from
40 up to 130 mm.

Float operated valves

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA" together with , or the abbreviated word mark .

Place of the mark:

- on the body.

Compulsory specifications:

- manufacturer name or logo
- reference to European Standard EN14124
- acoustical group (if applicable)

Method of marking:

- non-erasable;
- visible after assembly.

APPLICATION AND USE

Float operated valves are intended for use as filling valves for WC flushing cisterns, and designed for connection to potable water installations with a water temperature of 30 °C maximum and a working pressure of 1000 kPa maximum.

The float operated valves, intended for use as filling valves for flushing cisterns:

- are designed with an adjustment-device which shall guarantee the filling of the flushing cistern to a water level as indicated by the producer;
- shall open, after closing, within a decrease of the water level in the cistern of no more than 30 mm.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- WERIT Kunststoffwerke W.Schneider GmbH & Co. KG
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.