

Product certificate K12701/06

Issued 2016-11-01

Replaces K12701/05

Page 1 of 3

Close coupled suites

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Matel Hammadde Sanayî ve Tic. A.S.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline BRL-K621/06: "Close coupled suites", dated 01-02-2012

which covers the requirements of

EN 997: 2003 "WC-pans and WC suites with integral trap".



Luc Leroy
Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
P.O. Box 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl



Supplier

Matel Hammadde Sanayî ve Tic. A.S.
MANISA OSB 1. KISIM, KEÇİLİKÖY
MAH. ATATÜRK CAD. NO. 14
45030 YUNUSEMRE/MANISA
Turkey
Tel. +90 236 233 2452
Fax +90 236 233 2455

**Certification process
consists of initial and
regular assessment of:**

- quality system
- product

Close coupled suites

PRODUCT SPECIFICATION

The products mentioned below belong to this certificate.

The mentioned close coupled suites are designed for the use with a flush volume of 6 ± 0.2 litres, unless otherwise mentioned.

Model **LALE**

wash-down WC-pan no. 7602 with concealed vertical outlet (USV);
cistern Lale no. 7629 equipped with inner-mechanism manufacturer Idrols:

- flush-mechanism: Certified interruptible flushing mechanism 540406
- float operated valve type: Compact side servo

Model **LALE**

wash-down WC-pan no. 7606 with exposed horizontal outlet (UP);
cistern Lale no. 7629 equipped with inner-mechanism manufacturer Idrols:

- flush-mechanism: Certified interruptible flushing mechanism 540406
- float operated valve type: Compact side servo

Model **ANEMON**

wash-down WC-pan no. 5302 with concealed vertical outlet (USV);
cistern Anemon no. 5304 equipped with inner-mechanism manufacturer Idrols:

- flush-mechanism: Certified interruptible flushing mechanism 540406
- float operated valve type: Compact side servo

Model **ANEMON**

wash-down WC-pan no. 5306 with exposed horizontal outlet (UP);
cistern Anemon no. 5304 equipped with inner-mechanism manufacturer Idrols:

- flush-mechanism: Certified interruptible flushing mechanism 540406
- float operated valve type: Compact side servo

The hereafter mentioned close coupled suites are designed for the use with a nominal flush volume of 4 litres, complying with EN997: 2012

Model **DM02 DAMLA**

Wash-down WC-pan no. DM02 with concealed vertical outlet (USV);

Cistern no. 9448, equipped with inner-mechanism of manufacturer:

- flush-mechanism: Siamp Optima 49 dual flushing device
- float operated valve type: Siamp 95L

Delivered with matching fixing means.

Model **9402 LILA**

Wash-down WC-pan 9402 with concealed vertical outlet (USV);

Cistern no. 9448, equipped with inner-mechanism of manufacturer:

- flush-mechanism: Siamp Optima 49 dual flushing device
- float operated valve type: Siamp 95L

Delivered with matching fixing means.

Close coupled suites

APPLICATION AND USE

Close coupled suites are designed as flushing devices to be connected to drinking water installations with a maximum water temperature of 30 °C.

MARKING

The WC pan, cistern and float operated valve of the close coupled suites are marked with the wordmark "KIWA".

On the WC-pan this wordmark shall be followed by the number 6, 7.5 or 9, indicating the flushing volume.

For close coupled suite(s) with approved at a nominal flush of 4 or/and 5 litres, only the wordmark "**Kiwa**" is permitted.

Example:

Close coupled suite marked as follows:

*WC-pan: "**KIWA-6**"*

*Cistern: "**KIWA**"*

*Float valve: "**KIWA**"*

By this marking it is given that the close coupled suite is Kiwa certified and intended for use with a full flush of 6 ± 0.2 litres. This flushing volume is indicated by the highest waterline in the cistern.

Place of the mark:

- on the WC-pans between the attachment holes of the lavatory seat or on the sides;
- on the float valves on the body;
- on the cisterns on the left side, right side or front or on the inside above water level.

Compulsory specifications:

name or mark of the manufacturer:

- on the WC-pans between the attachment holes of the lavatory seat or on the sides;
- on the float valves on the body;
- on the cisterns on the left side, right side or front or on the inside above water level;
- additional markings as specified in EN 997 on a removable label.

Method of marking:

- indelible;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Matel Hammadde Sanayî ve Tic. A.S.

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.