

product certificate
K40105/03

Issued 2010-09-01
Replaces K40105/02
Page 1 van 4

Stop and connecting valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Gebr. Kemper GmbH + Co KG Metallwerke

comply with the technical specifications as laid down in this product certificate and are marked with the Kiwa®-mark as specified in this product certificate are, on delivery, relied upon to comply with Kiwa evaluation guideline

BRL-K604/05 "Stop and connecting valves",

which covers the requirements of

EN 1213: 1999 "Building valves - Copper alloy stopvalves for potable water supply in buildings - Tests and requirements".

Kiwa Nederland B.V.



ing. B. Meekma
Director

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid

Kiwa Nederland B.V.
Sir W. Churchill-laan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 70 414 44 00
Fax +31 70 414 44 20
E-mail info@kiwa.nl
www.kiwa.nl

Producer

Gebr. Kemper GmbH + Co KG Metallwerke
Harkortstraße 5
57462 OLPE
Germany
Phone +49 2761 8910
Fax +49 2761 891175
E-mail info@kemperolpe.de
Internet www.kemperolpe.de

**Certification process
consists of initial and
regular inspection of:**

- qualitysystem
- product

Stop and connecting valves

Products specification

The products mentioned below belong to this certificate

Red Brass models

135 01 – 135 02

DN 15
DN 25
DN 32
DN 40
DN 50
DN 65
DN 80
DN 100

173 0G – 173 1G

173 04 – 173 05, 173 08 – 173 09, 173 20 – 173-21,
173 30- 173 31
DN 15
DN 25
DN 32
DN 40
DN 50
DN 65
DN 80

173 40 – 173 41

DN 15
DN 25
DN 32
DN 40
DN 50

173 0K - 173 1K

DN 15
DN 25
DN 32
DN 40
DN 50

190 00 – 190 01

DN 15
DN 25
DN 32
DN 40
DN 50

190 22 – 190 23

DN 15
DN 25
DN 32
DN 40
DN 50

190 30 – 190 31

DN 15
DN 25
DN 32
DN 40

190 40 – 190 41

DN 15
DN 25
DN 32
DN 40

Stop and connecting valves

Products specification

The products mentioned below belong to this certificate

Red Brass / Brass models

174 0G – 174 1G

174 04 -174 05, 174 08 - 174 09, 174 20 – 174 21,

174 30 – 174 31

DN 15

DN 25

DN 32

DN 40

DN 50

174 40 – 174 41

DN 15

DN 25

DN 32

DN 40

174 0K – 174 1K

DN 15

DN 25

DN 32

DN 40

DN 50

191 00 – 191 01

DN 15

DN 25

DN 32

DN 40

DN 50

Stainless Steel models

073 00 – 073 01

073 0G – 073 1G

DN 15

DN 25

DN 32

DN 40

DN 50

Stop and connecting valves

Application and use

Straight-through and angle stop valves are intended to shut off conduit pipes of drinking water installations with a maximum water pressure of 1000 kPa and a water temperature of maximum 90°C.

Marking

The Kiwa[®]-mark products are marked with the wordmark "KIWA"

Place of the mark:

- on the body.

Compulsory specifications:

- name or mark of the manufacturer;
- nominal size DN;
- arrow indication direction of flow.

Method of marking:

- non erasable;
- visible after installation.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the producer has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Gebr. Kemper GmbH + Co KG Metallwerke

and, if necessary,

- Kiwa Nederland B.V.

Consult the producer's processing guidelines for the proper storage and transport methods.