

Product certificate
K41122/07

Issued 2014-12-15
Replaces K41122/06
Page 1 of 3

Stop and connecting valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by


Ankofit Industries B.V.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline BRL-K604/06: "Stop and connecting cocks",

which covers the requirements of

EN 1213: 1999: "Building valves - Copper alloy stop valves for potable water supply in buildings - Tests and requirements".



Bouke Meekma
Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
P.O. Box 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 70 414 44 00
Fax +31 70 414 44 20
info@kiwa.nl
www.kiwa.nl



288/130802

Supplier

Ankofit Industries B.V.
Edisonstraat 21
3861 NE NIJKERK GLD
The Netherlands
Tel. +31 33 246 07 04
Fax +31 33 246 02 60
info@ankofit.nl
www.ankofit.nl

Certification process consists of initial and regular assessment of:

- quality system
- product

Stop and connecting valves

PRODUCT SPECIFICATION

The products mentioned below belong to this certificate.

Stop valves with disc

Type	Size	
Art. 82910	12 mm x 12 mm	DN 10 C – C – S
Art. 82911	15 mm x 15 mm	DN 15 C – C – S
Art. 82912	22 mm x 22 mm	DN 20 C – C – S
Art. 82921	15 mm x 15 mm	DN 15 C – C
Art. 82922	22 mm x 22 mm	DN 20 C – C
Art. 82949	12 mm x 12 mm	DN 10 KF – KF – S
Art. 82951	15 mm x 15 mm	DN 15 KF – KF – S
Art. 82952	22 mm x 22 mm	DN 20 KF – KF – S
Art. 82961	15 mm x 15 mm	DN 15 KF – KF
Art. 82962	22 mm x 22 mm	DN 20 KF – KF

Connecting valves

Type	Size
According to technical drawing no. 70413	12mm x G3/8

REMARK

The specified products were not yet assessed for compliance with all ATA aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation materials and chemicals for drinking water and warm tap water supply"), implemented on 19 July 2011, as specified in clause 4.2.1 of the Kiwa evaluation guideline BRL-K604/06.

Stop and connecting valves

APPLICATION AND USE

Stop and connecting valves are designed to shut off, if desired temporarily, conduit pipes of drinking water installations intended for transporting drinking water with a maximum pressure of 1000 kPa and a water temperature with a maximum of 65°C. Using the products in water installations with a water temperature up to 90°C is possible. However, this may influence the durability of some parts and the contact temperature of the operation handle.

MARKING

The Kiwa[®]-mark products are marked with the word mark "KIWA" or the abbreviated word mark "KK".

Place of the mark:

- on the body.

Compulsory specifications:

- name or mark of the manufacturer, on the body;
- nominal size, DN, on the body;
- marking according to EN 1213, as applicable.

Method of marking:

- non erasable;
- visible after installation.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Ankofit Industries B.V.
and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.