





K41243/04 Replaces

1 of 3 Page



WC-pans

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Canakcilar Seramik A.S.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K619 "WC-pans" dated 15-09-2019.

which covers the requirements of

EN 997: 2012+A1:2015 "WC-pans and WC-suites with integral trap".

Ron Scheepers

Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands Tel. +31 88 998 44 00

Fax +31 88 998 44 20

NL.Kiwa.info@Kiwa.com

www.kiwa.nl

Company

Canakcilar Seramik A.S.

67670 GOKCEBEY ZONGULDAK

Turkey

Tel. +90 372 535 51 34

www.creavit.com.tr



Certification process consists of initial and regular assessment of:

- quality system
- product

page 2 of 3

WC-pans

Technical specification

The products mentioned below belong to this certificate.

The products mentioned are intended for connection with a (concealed)cistern, unless otherwise mentioned.

The products mentioned in this certificate are classified as Class 1 products unless otherwise mentioned.

WC-pans using a flush volume of 6 ± 0.2 litres

- Wall-hung WC-pan model FE320
 Wash-down Wc-pan with horizontal outlet
- Wall-hung WC-pan model TP320Wash-down WC-pan with horizontal outlet

page 3 of 3

WC-pans

Application and use

The WC-pans delivered under this certificate in combination with flushing cisterns and/or pressure flush valves are intended for use as sanitary appliances, connected to drinking water installations with a water temperature of 30 °C maximum.

Marking

The products are marked with the Kiwa-mark KIWA.

followed by:

- the number 6 or 7.5 or 9, which indicates the minimum necessary flush volume and
- the letter A and or C which indicates the type of flushing device to be connected:
 - A intended for connection with a cistern (or concealed cistern)
 - C intended for connection with a pressure flush valve.

Place of the mark:

 between the attachment holes of the lavatory seat or on one of the sides of the flushing rim of the WC pan.

Additional compulsory specifications:

name or mark of manufacturer:
 between the attachment holes of the lavatory seat or
 on one of the sides of the flushing rim of the WC pan.

Method of marking:

- indelible;
- visible after assembly.

Example:

The WC-pan is marked as follows:

"KIWA-6-A-C"

WC-pan intended for connection to a (concealed) flushing cistern or pressure flush valve. The minimum water volume required to perform

a full flush amount of 6 ± 0.2 litres.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Canakcilar Seramik A.S.
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.