



Product certificate K108913/01

Issued 2022-01-01

Replaces -

Page 1 of 3

Flushing cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

ALCA Plast s.r.o.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K620 "Flushing cisterns" dated 15-09-2019,

Which covers the requirements of

European Standard EN14055:2018 " WC and urinal flushing cisterns"

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

ALCA Plast s.r.o.
Biskupsky Dvur 2095/8
Nove Mesto, 110 00
Prague
Czech Republic
Tel. +420 627 333363

Certification process
consists of initial and
regular assessment of:

- quality system
- product



Flushing cisterns

PRODUCT SPECIFICATION

The products mentioned below belong to this technical approval-with-product certificate.

Concealed flush cistern (with panel control)

Sadromodul AM101/1120

With manual operation; including flush pipes and frame:

- inlet valve type A160, with side inlet connection brass G3/8
- outlet valve type Dual Flush no.TA06MOD
- flexible connecting hose type MN0115
- angled connecting valve type Schell, including check valve type Neoperl

Flushing cisterns

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA".

Place of the mark:

- on the cisterns on the left side, right side or front or on the inside above water level;
- on the body of the float operated valve (fitting valve).

Compulsory specifications:

- name or mark of the manufacturer:
 - on the float valves: on the body;
 - on the cisterns: on the left side, right side or front or on the inside above water level;
- reference as specified in the European Standard EN14055.

Method of marking:

- indelible;
- visible after assembly (for concealed flushing cisterns, after demounting of the control panel).

APPLICATION AND USE

Flushing cisterns (in combination with WC-pans) are designed as flushing devices to be connected to drinking water installations with a maximum pressure of 1000 kPa and a maximum water temperature of 30°C. Flushing cisterns using a nominal flush volume of 6 litres are intended for use in connection with WC-pans of the type 6A, according to guideline BRL-K 619.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- ALCA Plast s.r.o.

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.