



Product certificate K109347/02

Issued 2022-08-15

Replaces K109347/01

Page 1 of 2

Automatic shut-off (mixing) valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Hansgrohe SE

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K669 "Sanitaire kranen; zelfsluitende (meng)kranen" dated 01-12-2018.

which covers the requirements of

EN816:2017 "Sanitary tapware - Automatic shut-off valves PN 10"

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

288171015

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Hansgrohe SE
Auestrasse 5-9
77761 SCHILTACH
Germany
Tel. +49 7836 51-0
info@hansgrohe.com
www.hansgrohe.com



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Technical specification

Product mentioned below belong to the certificate

Model	Type	Acoustic group	Flow rate class
71.718.000	Talis Self-closing tap	I	O
71.719.000	Talis Self-closing tap	I	O

Remark

The above listed products were not yet assessed for compliance with all Hygienic aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation on materials and chemicals in drinking water and warm tap water supply), implemented on 01 July 2017, as specified in clause 4.2 of the Kiwa Evaluation guideline BRL-K669.

Application and use

The self-closing (mixer) taps are designed for application within the following limits of use:

- working pressure of maximum 1000 kPa;
- water temperature of maximum 90°C.

The recommended limits for correct operation are:

- working pressure of 100 kPa up to 500 kPa;
- water temperature of maximum 65°C

Marking

The Kiwa®-mark products are marked with the word mark "KIWA".

Place of the mark:

- on the body.

Compulsory specifications:

- name or mark of the manufacturer: on the body;
- indication of the acoustic group, if classified: on the body;
- indication of the flow rate class, if classified: on the body;
- indication for temperature selection (if applicable)

Method of marking:

- non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Hansgrohe SE
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.