





Issued 2022-06-01

Replaces

Page 1 of 3

Water pressure reducing valves (series 11-3103)

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Zhejiang Yorhe Intelligent Control Technology Co., Ltd

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline BRL-K14004/02: "Water pressure reducing valves and combination water pressure reducing valves", **d.d. 2002-04-19**

which covers the requirements of

EN1567:2002: "Building valves - Water pressure reducing valves and combination water pressure reducing valves – Requirements and tests".

Ron Scheepers

Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Supplier

Zhejiang Yorhe Intelligent Control Technology Co., Ltd 33 Fushan Road, Jiangong Building, 6/F, Block E Pudong Shanghai China

Tel: +86 576 8712 1722 Fax: +86 576 8712 1768 www.yhvalve.com sales@yhvalve.com

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273 P.O. Box 70 2280 AB RIJSWIJK The Netherlands

Tel. +31 88 998 44 00 Fax +31 88 998 44 20 info@kiwa.nl www.kiwa.nl

Certification process consists of initial and regular assessment of:

- quality system
- product

Page 2 of 3

Water pressure reducing valves

PRODUCT SPECIFICATION

The following products belong to this certificate;

- DN 15, DN 20 and DN 25;
- PN 10, 16;
- Temperature 30°C up to 80°C;
- Connection ends:
 - o Compression ends
 - o Internal threaded ends
 - o External threaded ends
 - o Push fit
 - o Press fit

Page 3 of 3

Water pressure reducing valves

REMARK

The above listed products were not yet assessed for compliance with all Hygienic Aspects as stated in the Dutch Drinking Water Decree and as outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Regulation on materials and chemicals in drinking water and warm tap water supply), implemented on 19 July 2011, as specified in clause 3.3 of the Kiwa Evaluation guideline BRL-K14004/01.

APPLICATION AND USE

Water pressure reducing valves and combination water pressure reducing valves, of nominal size DN 8 to DN 100, are intended use in drinking water installations with inlet pressures that do not exceed 1.600 kPa and a temperature that does not exceed 30°C for cold water applications and 80°C for hot water applications. Except when stated otherwise by the manufacturer, the valves can be applied for both temperature applications.

MARKING

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark: on the housing.

Compulsory specifications:

- name or logo of the manufacturer;
- nominal size (DN);
- an arrow for the direction of flow;
- · outlet pressure for special cases.
- In the countries where the use of products made of dezincification resistant materials is not required, the dezincification resistant products according to EN ISO 6509 as well as the products which do not contain zinc are allowed to be marked "DR".
- In the countries where the use of products made of dezincification resistant materials is required, the dezincification resistant products as well as the products which do not contain zinc shall be marked "DR".

Method of marking:

- · non-erasable;
- · visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Zhejiang Yorhe Intelligent Control Technology Co., Ltd and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.