



Product certificate K109598/01

Issued 2022-04-01

Replaces -

Page 1 of 2

Sanitary Tapware; Mechanical mixers

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Royal Oak International B.V.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K607 "Sanitary tapware; mechanical mixers" dated 10-10-2018, which covers the requirements of

EN 817: 2008: "Sanitary tapware – Mechanical mixers (PN10)".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Royal Oak International B.V.
Rollecate 3H
7711 GG Nieuwleusen
The Netherlands
e-mail: info@royal-oak.nl
tel: +31 650203687

Certification process
consists of initial and
regular assessment of:

- quality system
- product



Mechanical mixers

Technical specification

The products mentioned below belong to this certificate:

0321	Basin mixer
0322	Wall mounted mixer
0326	Basin mixer
0329	Sink mixer with swivel spout

REMARK

The above listed products were not yet assessed for compliance with all Hygienic Aspects as stated in the Dutch Drinking Water Decree and as outlined in the “Regeling materialen en chemicaliën drink- en warm tapwatervoorziening” (“Regulation on materials and chemicals in drinking water and warm tap water supply”), implemented on 19 July 2011, as specified in clause 4.2.2.1 of the Kiwa Evaluation guideline BRL-K607.

APPLICATION AND USE

The mechanical mixers are designed for application within following limits of use:

- working pressure from 50 kPa up to 1000 kPa;
- water temperature of maximum 70°C.

The recommended limits for correct operation are:

- working pressure of 100 kPa up to 500 kPa;
- water temperature of maximum 65°C.

MARKING

The Kiwa®-mark products are marked with the wordmark “KIWA”.

Place of the mark: on the body.

Compulsory specifications:

- name or mark of the manufacturer: Royal Oak on the body;
- indication for temperature selection: on the control device;
- the acoustic group, if classified: on the body;
- the flow rate class, on the body.

Method of marking:

- non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Royal Oak International B.V.

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.